



FINLAND'S INFORMATIVE INVENTORY REPORT 2025

**Air Pollutant Emissions 1980-2023
under the UNECE CLRTAP and the EU NECD**

Part 6 – Waste and Other Sources

March 2025

FINNISH ENVIRONMENT INSTITUTE

Climate solutions unit

Air pollution group

Finland's IIR

Part 6

Waste Sector and Other Sources

IIR - PART 6 – WASTE and OTHER SOURCES

6 WASTE (NFR 5)

- 6.1 Source category description
- 6.2 Solid waste disposal on land
- 6.3 Composting
- 6.4 Anaerobic digestion at biogas facilities
- 6.5 Waste Incineration (NFR 5C)
 - Municipal waste incineration
 - Industrial waste incineration including hazardous waste and sewage sludge
 - Clinical waste incineration
 - Cremation
- 6.6 Wastewater Handling (NFR 5D1, 5D2 and 5D3)
 - Domestic wastewater handling
 - Industrial wastewater handling
- 6.7 Other Waste (NFR 5E)

7 OTHER EMISSION SOURCES (NFR 6)

- 7.1 Other (NFR 6A)

Sub-chapters included under each NFR subcategory

Source category description

Emission trend

Methodological issues

Uncertainty and time series' consistency

Source-specific QA/QC and verification

Source-specific recalculations including changes in response to the review

Source-specific planned improvements

6 WASTE (NFR 5)

Changes in chapter	
March 2025	JMP, TF

6.1 Source category description

Emissions from solid waste disposal on land (landfills), composting, anaerobic digestion at biogas facilities, waste incineration, cremation, wastewater treatment, latrines and other waste (house and car fires) are included in under the Waste sector inventory as presented in Table 6.1.

Emissions from waste incineration are reported under NFR 1A1a or NFR 1A2gviii because all waste incineration occurring in Finland is with energy recovery.

Air pollutant emission levels from the waste sector are minor compared to the levels of greenhouse gases.

Table 6.1. Emission categories and reported emissions under NFR 5.

NFR	Processes	Description	Emissions reported
5 A	Biological treatment of waste – Solid waste disposal on land	Solid municipal, industrial, construction and demolition wastes	NMVOC, TSP, PM ₁₀ , PM _{2.5}
5 B 1	Biological treatment of waste – Composting	Biowaste, municipal solid waste, municipal and industrial sludges and industrial solid waste	NH ₃
5 B 2	Biological treatment of waste – Anaerobic digestion at biogas facilities	Covers biogas reactor plants at municipal and industrial wastewater treatment plants	NH ₃
5 C 1 a	Municipal waste incineration	No waste incineration occurs, all waste is combusted with energy recovery	-
5 C 1 bi	Industrial waste incineration		-
5 C 1 bii	Hazardous waste incineration	IE, emissions are allocated under energy sector, all waste incineration includes energy recovery	-
5 C 1 biii	Clinical waste incineration	Waste incineration occurred only in 1990-1993, all waste is combusted with energy recovery thereafter	-
5 C 1 biv	Sewage sludge incineration	No waste incineration occurs, all waste is combusted with energy recovery	-
5 C 1 bv	Cremation	Part of the emissions IE (under 1A1)	PM _{2.5} , PM ₁₀ , TSP, BC, Pb, Cd, Hg, As, Cr, Cu, Ni, Zn, PCDD/F, PAH-4, PCB, HCB
5 C 1 bvi	Other waste incineration	Not occurring	-
5 C 2	Open burning of waste	Not Occuring	-
5 D 1	Domestic wastewater handling	Wastewater handling, domestic, latrines	NMVOC, NH ₃
5 D 2	Industrial wastewater handling	Wastewater handling, industrial	NMVOC
5 D 3	Other wastewater handling	Not Occuring	-
5 E	Other waste	Car and house fires	PM _{2.5} , PM ₁₀ , TSP, BC, Pb, Cd, Hg, As, Cr, Cu, PCDD/F

Information on population as background data is presented in Table 6.2 for both urban and total population.

Table 6.2. Background data (total population and population in urban areas) related to the waste sectors (Statistic Finland, 2025).

Year	Total population	Urban population
1990	4 998 478	3 095 607
1995	5 116 826	3 242 380
2000	5 181 115	3 372 096
2005	5 255 580	3 491 993
2010	5 375 276	3 641 874
2015	5 487 308	3 797 978
2016	5 503 297	3 829 719
2017	5 51 3130	3 856 747
2018	5 517 919	3 881 481
2019	5 525 292	3 964 111
2020	5 533 793	3 992 546
2021	5 54 8241	4 012 715
2022	5 563 970	4 044 568
2023	5 603 851	4 093 493

6.2 Solid waste disposal on land (NFR 5A)

Changes in chapter	
March 2025	JMP, TF

Source category description

Under NFR 5A Finland reports NMVOC, TSP, PM₁₀ and PM_{2.5} emissions from disposal of solid municipal, industrial, construction and demolition wastes, as well as municipal (domestic) and industrial sludges. The emission reporting under the UNECE CLRTAP, the EU NECD and the UNFCCC are consistent.

The energy produced in waste incineration is utilised and the emissions are therefore reported in the Energy sector. Implementation of landfill gas recovery has also had a significant decreasing impact on the emissions.

The category is not a key category for any pollutants.

Emission trend

After the implementation of the revised Waste Act (1994), the Landfill Directive (1999/31/EC) and the ban of organic waste to landfills since 2016 (Government Decree 2013) minimisation of waste generation, recycling and reuse of waste material, landfill gas recovery and alternative treatment methods to landfills have been endorsed. Similar developments have occurred in the treatment of industrial waste, and municipal and industrial sludges. The increase of waste incineration has decreased the emissions from landfills from 2008 onwards.

Contribution of NFR 5A to total emissions and the shares of emissions reported by the plants are presented in Table 6.3.

Table 6.3. Contribution of Biological treatment of waste – solid waste disposal on land (NFR 5A) to total emissions in 2023.

Pollutant	Emissions from solid waste disposal on land	Total emissions	Unit	Share of total emissions %	% reported by the plants
NMVOC	0.064	72.510	Gg	<0.1	0
PM _{2.5}	<0.001	13.108	Gg	<0.1	0
PM ₁₀	<0.001	25.728	Gg	<0.1	0
TSP	0.001	39.531	Gg	<0.1	0

Methodological issues

NMVOC emissions

NMVOC emissions from solid waste disposal on land are calculated using the same method as in calculation of greenhouse gases described in the Finnish NID (http://www.stat.fi/tup/khkinv/khkaasut_raportointi_en.html), where methane emissions and the volume of landfill gas have been calculated using the First Order Decay (FOD) method.

The calculation of NMVOC emissions is based on the NMVOC concentration in landfill gas taking into account the recovery rate and other reductions. NMVOC concentration in the landfill gas is assumed to be 485 mg/m³ (Myllyperkiö, 2005) based on the average of studies carried out in the US in 1998 (Eklund. et al, 1998), in Germany in 1999 (Schweigkofler, 1999) and in Finland in 1990 (Asshuth, 1990), and has been estimated to correspond sufficiently to the Finnish conditions. In 2005 a study was carried out on the concentration because the Guidebook default value at that time, 5650 mg/m³, was considered unsuitable for the Finnish conditions. The study resulted in the value of 485 mg/m³, which still may overestimate a bit, but was considered much more suitable for domestic landfills. Since 2016, according to the Government decree on landfills (331/2013), only soil and rock material that can be used in the construction of the landfill site can be landfilled. Landfilling of other waste is not allowed but shall be recycled for the material or co-combusted for energy purposes.

The volume of landfill gas is derived from the density of methane (0.718 kg/m³) and from the fraction of CH₄ in landfill gas (0.5).

Activity data

The activity data used in the calculation are taken from the YLVA (formerly VAHTI) system. It includes information on all landfills in Finland excluding Åland, which is estimated according to the population. YLVA contains data on the total amounts of waste taken to landfills from 1997 onwards. In YLVA, the waste amounts are registered according to the EWC (European Waste Catalogue) classification (both EWC 1997 and EWC 2002). Sampling routines have been developed to convert the classification of the YLVA system to the classification used in the emission estimations. Corresponding data (but with volume units and a less detailed waste classification) for 1992 to 1995 were collected to the Landfill Registry of Syke. The activity data for municipal waste for 1990 are based on the estimates of the Advisory Board for Waste Management (1992) for municipal solid waste generation and treatment in Finland in 1989 with the correction of double counting in paper waste data (part of industrial paper waste was classified as municipal waste). The disposal data (amount and composition) at the beginning of the 1990s for industrial, construction and demolition

waste are based on surveys and research by Statistics Finland (Isaksson 1993; Puolamaa et al. 1995), VTT (Perälä & Nippala 1998; Pipatti et al. 1996) and the National Board of Waters and the Environment (Karhu 1993). For the base year, activity data from studies by Isaksson (1993) and Pipatti et al. (1996) are used for construction and demolition waste, by Karhu (1993 for industrial sludges, and by Puolamaa et al. (1995) for solid industrial waste. (Finland's NID 2025)

The amount of landfilled waste in is presented in Table 6.4. As it can be seen in Table 6.4 the amount of municipal solid waste has decreased significantly since 1990. This is due the increased energy use of wastes and this trend will continue in the future, also.

Table 6.4. Landfilled waste (1 000 t). Sources: YLVA database, Landfill Registry of the Finnish Environment Institute. Advisory Board for Waste Management 1992, Vahvelainen & Isaksson 1992, Isaksson 1993, Pipatti et al. 1996, Puolamaa et al. 1995, Perälä & Nippala 1998, Karhu 1993. (Finland's NID, 2025).

Waste group	1990	1995	2000	2005	2010	2015	2016	2017
Municipal solid waste	2 400	1 682	1 602	1 462	1095	318	78	19
Municipal sludge (d.m.)	47	25	6	6	3	5	1	0.2
Municipal sludge (wet m.)	498	298	70	53	22	14	7	3
Industrial sludge (d.m.)	337	260	118	48	26	7	3	4
Industrial sludge (wet m.)	1 193	881	550	161	82	20	10	10
Industrial solid waste	2 135	1 519	2 390	4 682	3135	2907	2862	2688
Constr. and demol. waste	1 262	637	454	390	349	163	102	112
Waste group	2018	2019	2020	2021	2022	2023		
Municipal solid waste	15	25	15	13	11	13		
Municipal sludge (d.m.)	0.1	0.1	0.1	0.1	0.1	0.0		
Municipal sludge (wet m.)	2	2	3	2	3	1		
Industrial sludge (d.m.)	3	2	4	2	2	1		
Industrial sludge (wet m.)	11	11	21	9	7	4		
Industrial solid waste	2629	2466	2622	2824	2474	3036		
Constr. and demol. waste	116	132	101	97	98	192		

Particle emissions

Particle emissions are calculated using the default emission factors from the EMEP/EEA Emission Inventory Guidebook 2023 (Table 3-1) and landfilled waste amounts (municipal and industrial solid waste and construction and demolition waste).

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out. The quality system is implied since the 2012 submission. At present, no verification has been carried out for the specific source-sector emissions.

Source-specific recalculations including changes made in response to the review process

2018

- Particle emissions were included in the inventory due to the recommendation from the 2017 NECD Review.

2020

- NMVOC 2017 were recalculated due to update in activity data (minor decrease in emissions)

2023

- More detailed information on estimation of NMVOC emissions from landfills is included.

Source-specific planned improvements

None.

6.3 Composting (NFR 5B1)

Changes in chapter	
March 2025	JMP, TF

Source category description

NH₃ emissions from composting are included in the category from year 1980 onwards. The shares of emissions for each air pollutant reported under the NFR category are presented in Table 6.5. The category is not a key category for NH₃.

Table 6.5. Contribution of Biological treatment of waste - Composting (NFR 5B1) to total emissions in 2023.

Pollutant	Emissions from composting	Total emissions	Unit	Share of total emissions %	% reported by the plants
NH ₃	0.073	30.160	Gg	0.2	0

Emission trend

The NH₃ emission trend from composting increased after the early 1990s due to the increased composting especially in semi-urban areas, which results from separate collection of organic waste. During the last ten years, the emissions have had a decreasing trend due to the growing share of anaerobic digestion. In 2019, the emissions increased due to changes in the treatment processes in a one major biological treatment plant.

Methodological issues

NH₃ emissions

The emissions are calculated for the whole time series using the emission factor presented in the EMEP/EEA Guidebook 2023 (Table3-1). The activity data is presented Table 6.6.

Table 6.6. Composted waste with auxiliary matter by subcategory (1000 t). (Finland's NID, 2025).

	1990	1995	2000	2005	2010	2015	2016	2017	2018	2019
Municipal solid waste	60	102	180	233	304	247	217	231	252	305
Municipal sludge (d.m.)	60	110	128	159	143	113	95	102	99	113
Industrial sludge (d.m.)	13	12	15	32	38	25	17	12	13	20
Industrial solid waste	12	18	31	45	60	24	40	34	49	51
	2020	2021	2022	2023						
Municipal solid waste	288	228	207	191						
Municipal sludge (d.m.)	95	91	66	65						
Industrial sludge (d.m.)	21	19	50	14						
Industrial solid waste	30	29	38	35						

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out. The quality system is implied since the 2012 submission. At present, no verification has been carried out for the specific source-sector emissions.

Source-specific recalculations including changes made in response to the review process

2009

- NH₃ emissions from composting were included in the inventory.

2016

- NMVOC emissions were recalculated for whole time series (1990 onwards) to be consistent with UNFCCC reporting.

2018

- NMVOC emissions were excluded from the inventory, because no default method is presented in the Guidebook and due to the recommendation of the 2017 NECD Review.
- The mistake in the calculation of NH₃ emissions (incorrect amount of industrial solid waste in 2015, value was corrected from 35 to 24 kt) observed during the 2017 NECD Review was corrected. The impact of the mistake was far below the threshold of significance for a technical correction (2%).

2020

- For year 2017 the amounts of composted waste were updated resulting in minor increase in NH₃ emissions. Due the lack of activity data the same amounts of composted waste were used for years 2017 and 2018.

2021

- Amounts of composted waste in 2018 were updated.

2022

- Amount of composted waste in 2019 were updated.

2023

- Amount of composted waste in 2020 were updated.

2024

- Amount of composted waste in 2021 were updated. During the NECD Review 2023 the TERT noticed that there was an inconsistency between the trend of NH₃ emissions and the development of activity data (kt composted) as reported in the NFR Tables for years 2019, 2020 and 2021. The AD in the NFR tables has been checked and corrected.

Source-specific planned improvements

None.

6.4 Anaerobic digestion at biogas facilities (NFR 5B2)

Changes in chapter	
March 2025	JG, TF, JMP

Source category description

The category covers NH₃ emissions from biogas reactor plants at municipal and industrial wastewater treatment plants, municipal solid waste biogas plants, sewage sludge plants and as farm-scale plants.

At the beginning of 2023, most of all biomethane and biogas was produced in plants using sewage sludge and biowaste as feedstock. The total number of biogas plants was 85: 34 farm-scale plants, 6 at industrial wastewater treatment plants, 28 biogas plants for co-treatment of municipal solid waste and sewage sludge, and 17 sewage sludge plants (Finnish Biocycle and Biogas Association, 2025)

The share of NH₃ emissions reported under the NFR category 5B2 are presented in Table 6.7. The category is not a key category for NH₃.

Table 6.7. Contribution of Biological treatment of waste – Anaerobic digestion at biogas facilities (NFR 5B2) to total emissions in 2023.

Pollutant	Emissions	Total emissions	Unit	Share of total emissions %	% reported by the plants
NH ₃	0.191	30.160	Gg	0.6	0

Emission trend

The NH₃ emission trend from biogas facilities has increased strongly after the early 2000s due to the increase in anaerobic treatment of sewage sludge, and because anaerobic treatment of other organic wastes (municipal organic waste, food waste, animal-based sludge) became more

common. The share of livestock manures is small, comprising approximately 10% of all produced biogas (in 2023).

Methodological issues

NH₃ emissions

The emissions are calculated for the whole time series using the emission calculation methods described in the EMEP/EEA Guidebook 2023. The calculation method has been nationally adjusted to account for the impact of the northern climate on emissions by incorporating a temperature factor into the formula.

Calculation includes NH₃ emissions from the following sources:

- storage of feedstock on the premises of the biogas facility,
- storage of the digestate.

For 5.B.2, the Tier 2 approach is used.

The Tier 2 approach estimates the total emission, E_{NH_3} (in kg NH₃ per year), from:

$$E_{NH_3} = AR_{feedstock} \times \sum_{stages} EF_{NH_3-N, stage\ i} \times 17/14 \times TempF$$

where,

$AR_{feedstock}$ = the total annual amount of N in feedstock, in kg a⁻¹;
 $EF_{NH_3-N, stage\ i}$ = the NH₃-N EF for stage i (i is the pre-storage, and storage of digestate) related to the total N in feedstock (kg NH₃-N per kg total N),
 $TempF$ = the temperature factor (0.8; see text below).

Emission factor of 0.0009 kg NH₃-N per kg N in feedstock is used for pre-storage of feedstock, and emission factor of 0.0266 kg NH₃-N per kg N in feedstock is used for storage of digestate.

The digestion of manures is calculated separately from the digestion of other organic wastes and of energy crops because the manure calculation in 5.B.2 is linked with the calculation of manure management (3.B) and manure application (3.D.a.2.a).

In the Finnish emission inventory, a temperature factor has been used in the ammonia emission calculations for manure management and application to account for the effect of Finland's cold climate compared to the climate of Central Europe, where emission measurements are typically conducted. However, the impact of temperature on emissions had not previously been considered in the calculation of emissions from the anaerobic digestion plants, but it was included in the reporting for 2025. The temperature factor of 0.8 is applied, corresponding to a six-degree Celsius difference in average temperature between Finland and Central Europe (see e.g. chapter 5.5.4 in the Agriculture section).

For digested manures, the TAN and total-N in manure (TAN_{sub} and N_{tot} respectively, kg a⁻¹) are:

$$TAN_{sub} = m_{biogas_slurry_TAN} + m_{biogas_solid_TAN}$$

$$N_{\text{sub}} = m_{\text{biogas_slurry_N}} + m_{\text{biogas_solid_N}}$$

where $m_{\text{biogas_slurry_TAN}}$, $m_{\text{biogas_solid_TAN}}$, $m_{\text{biogas_slurry_N}}$ and $m_{\text{biogas_solid_N}}$ are obtained from the manure management calculation module of the agricultural emission calculation system.

The TAN in digestate that is returned to agricultural emission calculation system is calculated using the equation:

$$m_{\text{dig_TAN}} = \text{TAN}_{\text{sub}} + f_{\text{min}} \times (N_{\text{tot}} - \text{TAN}_{\text{sub}}) - (E_{\text{NH}_3} \times 14/17)$$

where,

- $m_{\text{dig_TAN}}$ = TAN in digestate after storage in kg a^{-1} ,
- f_{min} = relative share of organic N entering the digester that is mineralized to TAN in the digester in kg kg^{-1} ,
- E_{NH_3} = NH_3 emitted in kg a^{-1} , calculated from total N.

The total-N in digestate that is returned to agricultural emission calculation system is:

$$m_{\text{dig_N}} = N_{\text{tot_dig}} - (E_{\text{NH}_3} \times 14/17)$$

Because no national data are available for f_{min} , a value of 0.32 for the N-mineralization of organic N in manures digested in biogas plants is used.

TAN flow for digestion is calculated separately for each animal category (see chapter 5.3 in Agriculture chapter).

For digested energy crops and waste, $N_{\text{tot,dig}}$ in digestate after storage is calculated using equation:

$$N_{\text{tot,dig}} = N_{\text{tot,sub}} - (E_{\text{NH}_3} \times 14/17)$$

where

- $N_{\text{tot,dig}}$ = Total amount of N in digestate after storage in kg a^{-1} ,
- $N_{\text{tot,sub}}$ = Total amount of N in the feedstock entering 5.B.2 in kg a^{-1} ,
- E_{NH_3} = Ammonia emitted during storage, in kg a^{-1} .

The value of $N_{\text{tot,dig}}$ is then used as a input data in 3Da2c (other organic fertilisers applied to soils) emission calculation.

Activity data

The amounts of anaerobically treated wastes are presented in Table 6.11.

The following total nitrogen (tot-N) concentrations ($\text{kg tot-N/kg biomass fresh weight}$) and dry matter content (% dry matter of fresh weight) are used for different anaerobically digested biomasses:

	kg N/kg FW	DM (% of FW)
Municipal organic waste	0.006	28%
Green waste	0.005	27%
Food waste (food processing)	0.005	40%
Sewage sludge	0.002	3%

Animal-based sludge	0.008	20%
Waste from beverage manufacturing	0.007	11%
Waste from bakeries	0.017	75%
Milk processing and milk waste	0.003	6%
Other grease waste	0.001	40%
Grass silage	0.008	30%
Grass from set-asides	0.005	40%
Straw	0.005	90%

The properties of food waste are sourced from the Guidebook, while the other values are based on the Final report of the biogas working group (Ministry of Economic Affairs and Employment 2020).

For the year 2023, the amounts of total nitrogen in the anaerobically digested masses were as follows (tonnes tot-N):

- Livestock manure: 713
- Municipal solid/organic waste: 1 480
- Municipal/sewage sludge: 3 402
- Industrial sludge (animal-based sludge): 448
- Industrial solid/organic waste (food waste): 1 106

Table 6.8. Anaerobically treated waste in 1990-2023 by subcategory (1000 t). (Finland's NID, 2025).

	1990	1995	2000	2005	2010	2015	2016	2017	2018	2019
Municipal solid waste	0	0	3.8	42.4	72.2	177.6	204.5	205.6	204.6	202.7
Municipal sludge (d.m.)	1.8	1.8	2.6	2.9	22.6	49.8	55.1	51.0	50.6	49.9
Industrial sludge (d.m.)	0	0	0	0.5	0.8	4.4	2.8	13.4	21.5	16.8
Industrial solid waste	0	0	0	5.0	66.1	80.4	108.4	119.0	131.4	116.1
	2020	2021	2022	2023						
Municipal solid waste	223.6	253.5	278.4	238.8						
Municipal sludge (d.m.)	54.4	66.9	59.3	60.5						
Industrial sludge (d.m.)	18.8	14.5	11.3	11.2						
Industrial solid waste	151.2	180.7	199.3	216.9						

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific recalculations including changes made in response to the review process

2022

- Calculation of NH₃ emissions included as response to the TERT 2019/2020 recommendations.

2023

- Amount of anaerobically treated waste has been updated for 2020.

2024

- Amounts of anaerobically treated wastes have been updated for the years 2014-2021, based on the data in the most recent Finland's NID, affecting the NH₃ emissions.
- The calculation of NH₃ emissions from the biological treatment of waste by anaerobic digestion at biogas facilities has been adjusted to include the manure that is removed from dry lots, which was erroneously excluded previously (only the manure managed in-house was considered). This adjustment slightly alters the results for the entire time series, particularly for animals where a portion of the manure ends up in the dry lot. Additionally, changes in nitrogen excretion rates of livestock animals also lead to some adjustments in NH₃ emissions from anaerobic digestion (see Chapter 5.4).

2025

- A temperature factor of 0.8 was added to ammonia emission calculation (see text).

Source-specific planned improvements

None.

6.5 Waste Incineration (NFR 5C)

Changes in chapter	
March 2025	JMP, TF

Source category description

All waste incineration in Finland includes energy recovery and the emissions are therefore reported under NFR 1A1a or NFR 1A2gviii. Only one waste incineration plant with no energy recovery has actually been in operation in Finland between the years 1969-1983 and these emissions are reported as IE under NFR 5C1a for the years 1980-1983. The only exception is ammonia, for which emission figures for 1980-1983 are reported under 5C1a. The emissions for this plant are based on data that the plant reported to the supervising authorities' data system YLVA.

The amount of landfilled municipal waste has decreased significantly (see Table 6.4 in chapter 6.2). The number of waste co-combusting plants with energy recovery has increased during the last decade for many reasons, e.g. due to implementation of the revised Waste Act, the revision of the Environmental Protection Act and the ban of organic waste to landfills since 2016 in addition to the rising cost of traditional fuels. Today there are more than 20 waste co-incineration plants in Finland. Typically, waste incineration occurs in peat and biomass firing boilers. The annual amount of waste co-incinerated is currently about 300,000 to 400,000 t/a. For more details, see IIR Part 2 Energy, chapter "Energy use of waste".

Under the NFR 5C waste incineration categories, the following emissions are reported:

- Particle, heavy metal, and POP emissions from cremation (NFR 5C1bv) from 1990 onwards
- Heavy metal and POP emissions from clinical waste incineration (NFR 5C1biii) for 1990-1993

Municipal waste incineration (NFR 5C1a)

Changes in chapter	
February 2024	KS, JMP

Source category description

All waste incineration in Finland includes energy recovery and the emissions are reported under NFR 1A1a or NFR 1A2gviii. The category is not a key category for any pollutants.

Methodological issues

SO₂, NO_x, NMVOC, particle and heavy metal emissions

SO₂, NO_x, NMVOC, particle and heavy metal emissions are reported by the plants according to the monitoring requirements in the environmental permits. In the cases where there are no reported emissions, the emissions are calculated from the fuel use of the plants with domestic emission factors. Details of the methodologies used in the emission estimation are presented in the IIR Part 2 Energy.

PCB and HCB

PCB and HCB emissions are calculated from the annually incinerated municipal solid waste (data available from Statistics Finland) using Guidebook 2023 emission factors. The emissions are reported under NFR 1A2gviii.

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out. The quality system is implied in the calculation of 2010 emissions.

Source-specific recalculations including changes made in response to the review Process

2015

- Emissions before 2011 were corrected by removing double values: NFR 5C1a to NE (includes emissions from WWTPs), the emissions were allocated under 5D1.

2016

- Ammonia, PCDD/F and PAH-4 emissions in 5C1a were revised for whole time series. In previous submissions Finland has reported emissions from clinical waste incineration (NFR 5C1biii) although actually no incineration of clinical waste in hospital sites has occurred after the year 1993. At the end of 1993 the new Waste Act (1994) and Environment Protection Act came in force, where after clinical waste has been managed in larger toxic waste disposal plants or landfilled. In 2016 landfilling has been forbidden and all clinical waste has to be incinerated in waste incineration plants.
- HCB, PCB and PCP from waste incineration were included in the inventory.

2018

- HCB and PCB emissions were recalculated using Guidebook 2016 emission factors for the whole time series.
- The notation key for waste incineration NFR categories were changed to NO.

2020

- update of emission factors for HCB and PCB according to Guidebook 2019.

2021

- update of activity data from 2015-2018.

Source-specific planned improvements

None.

Industrial waste incineration including hazardous waste and sewage sludge (NFR 5C1b)

Changes in chapter	
February 2025	JMP, TF

Source category description

All waste incineration in Finland includes energy recovery. The emissions are reported under NFR 1A1a or NFR 1A2gviii, while the methodology to calculate the emissions is presented below.

Methodological issues

SO₂, NO_x, NMVOC, Particle and heavy metal emissions

SO₂, NO_x, NMVOC, particle and heavy metal emissions are reported by the plants according to the monitoring requirements in the environmental permits in the YLVA database. In the cases where there are no reported emissions, the emissions are calculated from the fuel use of the plants with domestic emission factors. Details of the methodologies used in the emission estimation are presented in the IIR Part 2 Energy.

PCB and HCB emissions

PCB and HCB emissions are partly reported by the plants and have been completed with calculated emission data for those plants that do not report their emissions to the supervising authorities.

Amounts of incinerated industrial sludges are presented in Table 6.9 (source Statistics Finland for years 2004-2006 and for 2008-2023).

For years 1990-2003, 2007, and 2014 there is no official statistics available, that's why in the calculation it is assumed that 20% of the total incinerated industrial waste amounts were industrial sludges. When no official statistics available, waste amounts can be overestimated. According to an expert estimate (Espo, 2018) 10% of industrial sludges contains PCB for years 1990-2004, from 2005 onwards the percentage of PCBs containing sludges is 5 %. All PCBs and HCBs containing sludges are incinerated in waste incineration plants. HCB and PCB emissions are calculated for industrial sludges using the emission factor provided in the EMEP/EEA Guidebook 2023 (Table 3-2).

Table 6.9. Amount of incinerated industrial waste and industrial sludges (t) (Statistics Finland and Eurostat, 2025).

Year	Incinerated sludge (t)	Incinerated sludge containing PCB/HCB (t)
1990	299 288	29 929
1995	374 110	37 411
2000	446 687	44 669
2005	631 700	31 585
2010	503 000	25 150
2015	85 850	4 293
2016	49 619	2 481
2017	63 623	3 181
2018	131 526	6 576
2019	87 997	4 400
2020	94 356	4 720
2021	94 356	4 720
2022	48 840	2 442
2023*	48 840	2 442

*2022 values have been used

PCDD/F and PAH-4

PCDD/F and PAH-4 emissions are reported by the plants according to the monitoring requirements in the environmental permits in the YLVA database. In the cases where there are no reported emissions, the emissions are calculated from the fuel use of the plants with domestic emission factors. Details of the methodologies used in the emission estimation are presented in the IIR Part 2 Energy.

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out.

Source-specific recalculations including changes made in response to the review Process

2018

- HCB and PCB emissions recalculation using Guidebook 2016 methods

2021

- Update of activity data prior to 2015, the earlier years are expert estimates

2022

- Update of activity data for 2019

2024

- Update of activity data for 2020

2025

- Update of activity data from 2020 onwards

Source-specific planned improvements

None.

Clinical waste incineration (NFR 5C1biii)

Changes in chapter	
March 2025	JMP, TF

Source category description

Clinical waste incineration occurred in Finland until 1994, where after clinical waste incineration units were closed down. Thereafter clinical waste was treated in a large toxic waste disposal plant or landfilled. From 2016 onwards clinical waste has been co-combusted in energy production plants. Thus, emissions prior to 1994 are reported under NFR 5C1biii and from the year 1994 onwards under NFR 1A1a or 1A2gviii.

The allocation of emissions was changed in the 2018 submission because all waste incineration in Finland has included energy recovery after the year 1993. This is due to the implementation of the 1994 Waste Act and the revised Environmental Protection Act, which came into force and resulted in a change also regarding clinical waste management. According to the legislation, clinical waste had to be managed in larger toxic waste disposal plants or landfilled, and in 2016 landfilling was also forbidden.

The category is not a key category for any pollutants.

Methodological issues

Activity data

Activity data is an assumption based on an expert estimate (SYKE/Merilehto Kirsi, 2000 Table 6.10).

Table 6.10. Volume of incinerated clinical waste 1990-1993 (expert estimate, Merilehto 2000).

Year	Waste amount
1990	10 000 t
1991	10 000 t
1992	10 000 t
1993	10 000 t

Heavy metals

Heavy metals emissions from 1990-1993 are reported by the plants according to the monitoring requirements in the environmental permits.

POP compounds

PCDD/F, PAH-4, HCB and PCB emissions for the years 1990-1993 are calculated with the following emission factors, which are assumed to be more suitable for the Finnish conditions in the early 1990s than the Guidebook EFs. The EFs in the Guidebook are presented in the brackets. Note, that for PCB, Guidebook emission factors have been used since no other EFs have been available.

PCDD/F	7 µg I-TEQ /t (Syke, 2001)	(Guidebook 2023, 3 mg I-TEQ/Mg)
PAH-4	20 mg/t (EEA, 2002)	(Guidebook 2023, 0.04 mg/Mg)
HCB	2.9 mg/t (Bailey, 2001)	(Guidebook 2023, 0.1 g/Mg)
PCB	20 mg/t	(Guidebook 2023)

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out.

Source-specific recalculations including changes made in response to the review Process

2016

- Emissions from year 1994 onwards were included in NFR 5Ca1. In the 1990-2015 submissions emissions from clinical waste incineration (NFR 5C1 biii) were erroneously reported although no incineration of clinical waste occurred at hospital sites after the year 1993.

2018

- The notation key was changed to "NO" from 1994 onwards.

Source-specific planned improvements

None.

Sewage sludge incineration (NFR 5C1biv)

No sewage sludge incineration occurs in the country.

Cremation (NFR 5C1bv)

Changes in chapter	
March 2025	JMP, TF

Source category description and explanation of emission trends

Emissions from cremation are calculated from 1990 onwards. The shares of emissions for each pollutant reported under the NFR category are presented in Table 6.11.

Cremation is a key category for mercury emissions according to the level and trend (Approach 1). NO_x, NMVOC, SO_x are reported under 1A1a/1A2gviii.

Table 6.11 Contribution of Cremation (NFR 5C1bv) to total emissions in 2023.

Pollutant	Tier	Emissions from cremation	Total emissions	Unit	Share of total emissions %	% reported by the plants
PM _{2.5}	T1	0.001	13.108	Gg	<0.1	0
PM ₁₀	T1	0.001	25.728	Gg	<0.1	0
TSP	T1	0.002	39.531	Gg	<0.1	0
BC	T1	<0.001	3.063	Gg	<0.1	0
Pb	T1	0.001	12.089	Mg	<0.1	0
Cd	T1	<0.001	0.767	Mg	<0.1	0
Hg	T2/T3	0.025	0.493	Mg	5.1	0
As	T1	<0.001	1.632	Mg	<0.1	0
Cr	T1	<0.001	13.473	Mg	<0.1	0
Cu	T1	<0.001	37.478	Mg	<0.1	0
Ni	T1	<0.001	8.793	Mg	<0.1	0
Se	T1	<0.001	0.440	Mg	0.2	0
Zn	T1	0.006	119.511	Mg	<0.1	0
PCDD/F	T1	0.001	8.651	g I-Teq	<0.1	0
PAHs	T1	0.001	19.315	Mg	<0.1	0
HCB	T1	0.006	16.240	kg	<0.1	0
PCBs	T1	0.016	14.315	kg	0.1	0

Emission trend

Cremation was not common in Finland in the 1990s and the number of cremations has gradually been increasing only since the beginning of the 2000s (Figure 6.4). Due to the low number of cremations, the first abatement technique (activated carbon filters) in a crematorium was installed in 2013. Since 2020 activated carbon filters have been used in seven out of the thirteen existing crematoria, while there is no abatement technique in the rest of the crematoria. The numbers of cremations each year in each of these 13 crematoria are available from the association of Finnish Congregations.

Methodological issues

Mercury emissions from crematoria

The use of amalgam in dental fillings has been low before the 1950s in Finland and then it has decreased again since the early 2000s to almost zero today, being in 2013 only 3% of all fillings. In 2018 a ban of amalgam (EU Regulation 2017/852) was stipulated for persons of 15 years old or

younger as well as for pregnant women. Most amalgam fillings in teeth have those born in 1940-1950, i.e. those currently older than 65 years.

In the calculation, the population numbers from 1990 have been divided into 3 groups: those older than 65 years, those 15-64 years and those younger than 15 years. For these three groups, the factors of 1, 0.5 and 0 have been used to quantify the cremations including amalgam tooth fillings: all in the age group >65 years, half of the age group 15-64 years and none in the age group <15 yrs. This may still lead into an overestimate (e.g. due to missing teeth). but is a considerably smaller overestimation than using only the Tier 1 emission factor for all cremations.

The emission factor of 1.48 g/cremation (without abatement from EMEP/EEA Guidebook 2023) has been used for crematoria without abatement technique and the country specific emission factor of 0.59 g Hg/cremation for those cremations in crematoria with activated carbon filters. The country specific emission factor is based on Swedish emission measurements¹, which result in concentrations below 0.1 mg/m³(n), the removal efficiency of the activated carbon filters being 96-99.5% (Wängberg, 2013).

Activity data

The number of incinerated corpses is received from the Finnish Congregations (Finnish Congregations, 2024) by each crematoria, and out of these an annual share is calculated from cremations in crematoria with abatement and those without abatement (Table 6.12)

Table 6.12. Cremations per year and annual shares with/without abatement (activated carbon).

Year	All	Without abatement	With abatement	Share abated
1990	8 000	8 000	0	0
1995	9 774	9 774	0	0
2000	13 084	13 084	0	0
2005	16 108	16 108	0	0
2010	21 068	21 068	0	0
2015	25 631	19 839	5 792	0.226
2016	27 483	18 600	8 883	0.323
2017	28 336	17 877	10 459	0.369
2018	29 550	17 539	12 011	0.406
2019	30 733	18 504	12 229	0.398
2020	33 246	19 249	13 296	0.400
2021	34 861	20 513	14 348	0.416
2022	39 235	23 683	15 552	0.396
2023	39 076	21 514	17 562	0.449

Particles, POPs and heavy metals

All emissions are calculated with the EMEP/EEA Guidebook 2023 EFs (Table 3-1).

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

¹ Source: Swedish IIR 2022. The emission level of 0.59 g Hg/cremation has been verified by the Finnish Crematoria Foundation.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out.

Source-specific recalculations including changes made in response to the review Process

2013

- Inclusion of heavy metal emissions

2017

- The method was revised to the emission factors from the 2013 Guidebook to 2016 for the whole time series.

2020

- A country-specific method for calculation of Hg emissions was developed.

2021

- Incorrect Hg calculation file used in 2020 reporting has been revised for whole time series.

Source-specific planned improvements

None

Other waste incineration (NFR 5C1bvi)

No “other” waste incineration occurs in the country.

Open burning of waste (NFR 5C2)

Source category description

Incineration in households is forbidden according to the Environmental Protection Act and therefore no emissions are expected from this category.

On the request of the 2020 TERT we calculated the emission levels that would result from open burning of garden waste. Household and other “real” waste is not burned in Finland and forest residues are collected to industry or household energy purposes or left in the forest to improve soil or diversity of species. Using EFs in Table 3.3 of the 2019 Guidebook we conclude that the emissions would be below 0.0001% of national totals for all pollutants and thus insignificant.

From several national reports on household waste published in 2004-2019 we conclude that open burning of garden waste is happening occasionally and seasonally in the sparsely populated areas in small amounts as explained below. The amount of garden waste is estimated as 10 kg/inhabitant/year, while the population in sparsely populated areas is about half a million, half of these inhabitants burn garden waste occasionally and the amount that then is burned is 0.1% of

the amount of garden waste. Instead of burning, twigs and branches are mostly composted, chipped, used as soil enrichment/building and in more densely populated areas mainly brought to recycling facilities for composting. Twigs and branches that are of sensible size to burn are preferably combusted as fuel in small combustion equipment as almost all dwelling houses, especially in the sparsely populated areas, have these equipment.

In Finland open burning of waste is forbidden and the offender will be fined as there are strict municipal orders about this. Everywhere in the country, also in sparsely populated areas, you are not allowed to cause nuisance to neighbours or danger of fire and you are fully responsible of any damage caused. In the sparsely populated areas, taking into account all above, it is possible to burn small amounts of dry twigs and branches on your own land. You can only burn in small batches similar to small campfires during the light time of the day and you need to have fire-fighting equipment and arrange guarding of the embers after the flames have died.

Source-specific recalculations including changes made in response to the review Process

2020

- This chapter (NFR 5C2) was accidentally removed when the IIR was thoroughly updated in the recalculation processes in 2018 and 2019 and is now returned to the IIR.

6.6 Wastewater Handling (NFR 5D)

Source category description

The emission sources under category 5D cover municipal (domestic) and industrial wastewater handling plants, latrines and septic tanks. Emissions from wastewater treatment have been declining since 1990 due to increasingly efficient treatment of wastewater which has also been implemented in sparsely populated areas, as well as a lower nitrogen burden released from industrial wastewaters into waterbodies.

Domestic wastewater handling (NFR 5D1)

Changes in chapter	
March 2025	JMP, TF

Source category description

NM VOC emissions from domestic wastewater handling and NH₃ emissions from latrines are reported under this category. The category is not a key category for any pollutants.

In Finland there are approximately 350 municipal wastewater treatment plants, in each of them wastewater from more than 100 people is treated based on environment permits. (Finnish Water Utilities Association, FIWA, 2023).

The shares of emissions for each air pollutant reported under the NFR category are presented in Table 6.13.

Table 6.13. Contribution of Domestic wastewater handling (NFR 5D1) to total emissions in 2023.

Pollutant	Tier	Emissions from domestic wastewater handling	Total emissions	Unit	Share of total emissions %	% reported by the plants
NMVOC	T1	0.008	72.510	Gg	<0.1	0
NH ₃	T2	0.379	30.160	Gg	1.3	0.8

The same NMVOC emissions that are reported under the UNECE CLRTAP and the EU NECD are also reported under the UNFCCC, thus the activity data and methods used in the calculations are the same.

Emission trend

The increase in NH₃ emissions is due to the increase in number of summer cottages (used as AD in the estimation of NH₃ emissions from latrines). The NMVOC emissions follows the amounts of handled wastewater which varies between years.

Methodological issues

Domestic wastewater treatment

NMVOC emissions

NMVOC emissions are calculated using the Tier 1 method presented in the EMEP/EEA Guidebook 2023 (Table 3-1, page 7). Activity data is taken from YLVA database as presented in Table 6.14. The activity data by plants is annually available from YLVA.

NH₃ emissions

NH₃ emissions from domestic wastewater treatment are reported by the plants. There is no methodology for estimating NH₃ emissions in the EMEP/EEA Guidebook 2023.

Table 6.14. Handled domestic wastewater 1990-2023 (1000 m³).

Year	handled domestic wastewater (1000 m ³)
1990	213 801
1995	281 343
2000	575 409
2005	550 630
2010	511 092
2015	580 839
2016	551 201
2017	673 677
2018	580 090
2019	823 903
2020	596 283
2021	535 309
2022	466 677
2023	543 042

Latrines

NH₃

NH₃ emissions from latrines are calculated according to the Tier 2 methodology of the EMEP/EEA Guidebook 2023 (Table 3-2, page 8). Latrines are mainly used at summer cottages in Finland. It is assumed that latrines exist at 70% of summer cottages and are used by approximately 2 persons during the summer months, i.e. 4 months per year. The number of summer cottages is presented in Tables 6.15.

Table 6.15. Number of summer cottages in Finland 1980-2023 (Statistics Finland, 2024).

Year	Number of summer cottages	Year	Number of summer cottages
1980	251 744	2018	509 800
1985	251 744	2019	511 990
1990	367 686	2020	508 000
1995	416 236	2021	508 919
2000	450 569	2022	509 652
2005	474 277	2023	503 753
2015	501 600		
2016	502 900		
2017	507 200		

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out.

Source-specific recalculations including changes made in response to the review process

2016

- Previously NMVOC emissions from industrial and domestic wastewater handling were reported aggregated under NFR 5D3 Other wastewater handling and have since the 2016 submission been reported under NFRs 5D1 and 5D2.

2018

- The recommendation of the 2017 NECD Technical Review to revise the method to calculate NMVOC emissions could not be implemented because the wastewater volume data is not accurate enough to implement the method from the 2016 Guidebook. The current method is considered to be more accurate and is also consistent with the one used in the greenhouse gas reporting.

2019

- NMVOC emissions are calculated as described Guidebook 2019.

2020

- Ammonia emissions from some point sources was accidentally excluded in the 2019 submission for the years 2012, 2014 and 2015. The missing NH₃ emissions have been included in the 2020 submission and increased slightly the emissions.

2021

- Reallocation of latrines from NFR 5E to NFR 5D1.

2024

- Activity data for domestic wastewater treatment was updated for year 2005 and from year 2010 onwards as a result of the 2023 NECD Technical Review.

Source-specific planned improvements

None.

Industrial wastewater handling (NFR 5D2)

Changes in chapter	
March 2025	JMP, TF

Source category description

The shares of emissions for each air pollutant reported under the NFR category are presented in Table 6.16. The category is not a key category for any pollutants.

Table 6.16 Contribution of Industrial wastewater handling (NFR 5D2) to total emissions in 2023.

Pollutant	Tier	Emissions from industrial wastewater handling	Total emissions	Unit	Share of total emissions %	% reported by the plants
NMVOG	T1	0.013	72.510	Gg	<0.1	0

The NMVOC emissions reported under the UNECE CLRTAP and the EU NECD are also reported under the UNFCCC and the activity data and methods used in the calculation are the same.

Emission trend

The NMVOC emissions follow the amounts of handled industrial wastewater which varies between years.

Methodological issues

NMVOG emissions

NMVOG emissions are calculated using the Tier 1 method presented in the EMEP/EEA Emission Inventory Guidebook 2023 (Table 3-1, page 7). Activity data is taken from YLVA database and presented in Table 6.17. The activity data by plants is annually available from YLVA. For some plants, the reported wastewater also includes cooling water. These are corrected manually in the calculation. However, the number of these plants is small.

Table 6.17 Handled industrial wastewater 1990-2023 (1000 m³). (YLVA database)

Year	Handled industrial wastewater (1000 m ³)
1990	1 433 445
1995	1 415 457
2000	1 356 726
2005	1 063 866
2010	956 915
2015	909 001
2016	966 315
2017	1 034 360
2018	1 255 103
2019	1 220 300
2020	1 1452 55
2021	1 123 640
2022	821 103
2023	887 257

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out.

Source-specific recalculations including changes made in response to the review process

2016

- Previously NMVOC emissions from industrial and domestic wastewater handling were reported aggregated under NFR 5D3 Other wastewater handling and have since the 2016 submission been reported under NFRs 5D1 and 5D2.

2018

- The recommendation of the 2017 NECD Technical Review to revise the method to calculate NMVOC emissions could not be implemented because the wastewater volume data is not accurate enough to implement the method from the 2016 Guidebook. The current method is considered to be more accurate and is also consistent with the one used in the greenhouse gas reporting

2019

- NMVOC emissions are calculated as described Guidebook 2019.

2024

- Activity data for domestic wastewater treatment was updated for year 2005 and from year 2010 onwards as a result of the 2023 NECD Technical Review.

Source-specific planned improvements

None

Other Wastewater handling (NFR 5D3)

Changes in chapter	
March 2021	KS, JMP

No “other” wastewater handling occurs in the country.

Source-specific recalculations including changes made in response to the review process

2016

- The allocation of NMVOC emissions under NFR categories was checked to be consistent with UNFCCC CRF categories since the 2016 submission. NMVOC emissions from wastewater handling previously reported under NFR 5D3 Other wastewater handling are now reported under NFRs 5D1 and 5D2 for the whole time series.

2018

- The notation key was changed from “NA” to “NO”.

6.7 Other waste (NFR 5E)

Changes in chapter	
March 2025	JMP, TF

Source category description

NFR 5E Other covers particle, PCDD/F and heavy metal emissions from house and car fires. The shares of emissions for each air pollutant reported under the NFR category are presented in Table 6.18.

Other waste is a key category for PCDD/F emissions according to the level and trend (Approach 1).

Table 6.18. Contribution of Other waste (NFR 5E) to total emissions in 2023.

Pollutant	Tier	Emissions from other waste	Total emissions	Unit	Share of total emissions %	% reported by the plants
PM _{2.5}	T2	0.116	13.108	Gg	0.9	0
PM ₁₀	T2	0.116	25.728	Gg	0.5	0
TSP	T2	0.116	39.531	Gg	0.3	0
BC	T2	0.010	3.063	Gg	0.3	0
Pb	T2	<0.001	12.089	Mg	<0.1	0
Cd	T2	<0.001	0.767	Mg	<0.1	0
Hg	T2	<0.001	0.493	Mg	0.1	0
As	T2	0.001	1.632	Mg	<0.1	0
Cr	T2	0.001	13.473	Mg	<0.1	0
Cu	T2	0.003	37.478	Mg	<0.1	0
PCDD/ F	T2	1.214	8.651	g I-Teq	14.0	0

Emission trend

The emission trends follow the number house and car fires available in the statistics.

Methodological issues

Car and house fires

Particles

Emissions from house and car fires are calculated using Tier 2 emission factors from the EMEP/EEA Guidebook 2023 with the EF of 2.3 kg/fire (TSP, PM₁₀, PM_{2.5}).

Heavy metals

The emissions are calculated using Tier 2 emission factors from EMEP/EEA Guidebook 2023 (Table 6.19).

Table 6.19. Emission factors for heavy metals and PCDD/F from house fires.

Pollutant	Unit	Emission factors for house fires (EMEP/EEA Guidebook 2023), Tier 2			
		Detached houses	Undetached houses	Apartment buildings	Industrial buildings
TSP	kg/fire	143.82	61.62	43.78	27.23
PM ₁₀	kg/fire	143.82	61.62	43.78	27.23
PM _{2.5}	kg/fire	143.82	61.62	43.78	27.23
Pb	g/fire	0.42	0.18	0.13	0.08
Cd	g/fire	0.85	0.36	0.26	0.16
Hg	g/fire	0.85	0.36	0.26	0.16
As	g/fire	1.35	0.58	0.41	0.25
Cr	g/fire	1.29	0.55	0.39	0.24
Cu	g/fire	2.99	1.28	0.91	0.57
PCDD/F	mg/fire	1.44	0.62	0.44	0.27

PCDD/F

The Tier 2 emission factor of 0.048 mg/fire from EMEP/EEA Guidebook 2023 is used for car fires. For house fires, the Tier 2 emission factor presented in Table 6.27 is used.

Activity data

Activity data for 1990-2023 is presented in Table 6.20.

For house fires, it is assumed based on information from Rescue Services' Fire Statistics (2021) that:

- 25% of house fires are un-detached house fires,
- 5% detached house fires,
- 23% apartment building fires and
- 47% industrial building fires

In addition, it is assumed that all other fires that are not house or apartment building fires, are industrial building fires. In the Fire Statistics industrial buildings consists of several different building types for example office buildings, industrial buildings and farm buildings.

The Fire Statistics were changed in 2009 resulting in a lower number of house fires compared to the previous years.

According to the statistics of the Rescue Services (2019), approximately 94% of vehicle fires are road vehicles fires, 2% off-road vehicles and 2% watercraft fires. Less than one per cent of the fires are railroad vehicle or airplane fires.

Table 6.20 Activity data: vehicle and house fires (Rescue Services, 2024)

Year	Vehicle fires	House fires
1990	2 490	6 010
1995	1 800	3 500
2000	2 377	3 134
2005	2 630	3 670
2010	2 438	2 789
2015	2 200	2 010
2016	2 262	2 164
2017	2 081	2 106
2018	2 335	2 018
2019	2 186	2 053
2020	2 068	1 857
2021	2 179	1 959
2022	2 131	1 888
2023	2 068	1 800

Uncertainty and time series' consistency

The results of the uncertainty analysis are presented in Annex 6 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checking related to the assessment of the magnitude and trends has been carried out.

Source-specific recalculations including changes made in response to the review process

2009

- PCDD/F and PCB emissions from unintentional landfill fires were included.

2013

- NH₃ emissions from latrines were included.

2015

- Emissions from car and house fires were moved from NFR 2G (NFR09) to NFR 5E (NFR2014).

2016

- Emissions from car and house fires were recalculated as the result of correction of emission factors in Guidebook 2016. As described in Guidebook: *Personal contact with Kristin Aasestad has provided a correction of the units which are inaccurate in the text of Aasestad (2007). Previously EFs from Norwegian IIR has been used and the EF as a result of wrong unit has been 1000x to small. Black carbon emissions from house fires are calculated using emission factor 9% of PM2.5 (Aasestad, 2013).
- Emissions were reallocated to the NFR 5E from NFR 2G from the year 2014 emissions.

- Emissions from car, house and unintentional landfill fires are included in the inventory in the NFR 5E.

2017

- NH₃ emissions from latrines was reallocated to 5E, however, the change was done only for years 2014 and 2015 emissions.
- Heavy metal emissions from NFR 5E (house and car fires) were updated according to the Guidebook 2016.

2018

- No methodology is provided in the Guidebook to estimate emissions from landfill fires. The method used to calculate all emissions in the earlier submissions was considered to be uncertain and the emissions were removed to this submission.

2021

- Reallocation of latrines from NFR 5E to NFR 5D1.

2023

- The error in calculation of vehicle fires was corrected in line with the TERT recommendation in the 2022 NECD review. In the earlier submissions it was assumed that out of vehicle fires 68% were passenger car fires and the emissions were calculated only for passenger car fires. In the 2023 submission the calculation was changed to cover emissions of fires of all vehicle types.

2024

- The percentage distribution of total house fires was revised due the recommendation of the TERT in the 2023 NECD review. In the earlier submissions it was estimated that 26% of house fires are un-detached house fires, 4 % detached house fires, 10% apartment building fires and 18% industrial building fires. The fires did not sum to 100% but only 58%. For the 2024 submission, the percentage distribution was corrected to sum to 100%.

Source specific planned improvements

- Possibilities to include HCB emissions from landfill fires to the inventory are studied.
- Possibilities to calculate emissions from vehicle fires using methods presented in Denmark's IIR 2021 will be further studied.

7 OTHER EMISSION SOURCES (NFR 6)

Changes in chapter	
March 2025	JG, TF, JM

7.1 Other sources (NFR 6A)

Source category description

This source category includes ammonia emissions from animals that cannot be attributed to the agricultural or natural sectors. Because in the Finnish emission inventory all horses - including agricultural, recreational, and racing horses - are included in the agriculture sector, this category considers only pets, i.e., cats and dogs. The share of ammonia emissions from this category to the

national total is presented in Table 7.1. This is a key category for ammonia emissions according to the trend of emissions (Approach 1).

Table 7.1 Contribution of Other sources (NFR 6A) to total emissions in 2023.

Pollutant	Tier	Emissions from other sources	Total emissions	Unit	Share of total emissions %	% reported by the plants
NH ₃	T1	0.603	30.160	Gg	2	0

Emission trend

The ammonia emission trends follow the trends in the activity data (Table 7.2). During the Covid pandemic, there was an increase in pet ownership, which explains at least part of the rising emissions trend.

Methodological issues

The calculation adheres to the Tier 1 default approach outlined in the EMEP/EEA Guidebook 2023, focusing solely on ammonia emissions. The calculation method has been nationally adjusted to account for the impact of the northern climate on emissions by incorporating a temperature factor into the formula.

The emission of NH₃ from pets is estimated as follows:

$$E_{pets} = \sum (EF_{pet,i} * AAP_{pet,i}) \times TempF$$

where:

- E_{pets} = total emission of NH₃ from pets (in kg a⁻¹),
- $EF_{pet,i}$ = emission factor of pet i (kg NH₃ a⁻¹ AAP⁻¹),
- $AAP_{pet,i}$ = annual average population of pet i (a⁻¹),
- TempF = temperature factor (see text).

Ammonia emission factors of Sutton et al (2000)² are applied:

- 0.13 kg NH₃ a⁻¹ AAP⁻¹ for cats,
- 0.74 kg NH₃ a⁻¹ AAP⁻¹ for dogs.

In the Finnish emission inventory, a temperature factor has been used in the ammonia emission calculations for e.g. manure management and application to account for the effect of Finland's cold climate compared to the climate of Central Europe, where emission measurements are typically conducted. However, the impact of temperature on emissions had not previously been considered in the calculation of emissions from cats and dogs, but it was included in the reporting for 2025. The temperature factor for cats is 1 because cats are usually kept indoors so that the outdoor temperature does not affect ammonia volatilisation. For dogs, a temperature factor of 0.8 is applied, corresponding to a six-degree Celsius difference in average temperature between Finland and Central Europe (see e.g. chapter 5.5.4 in the Agriculture section).

² Sutton M.A., Dragosits, U., Tang, Y.S. and Fowler, D. 2000. Ammonia emissions from non-agricultural sources in the UK, Atmospheric Environment 34 (2000) 855-869.

Activity data

Data on cat and dog population (Table 7.2) is based on the following sources and assumptions:

• Cats

- years 1980-1997: estimate based on the population number of the year 1998,
- year 1998: single estimate found from the internet,
- years 1999-2015: linear trend assumed between the years 1998 and 2016,
- year 2016: Statistics Finland (https://www.stat.fi/til/ktutk/2016/ktutk_2016_2020-04-20_tie_001_en.html),
- years 2017-2020: linear trend assumed between the years 2016 and 2021,
- years 2021 and 2022: FEDIAF EuropeanPetFood (<https://europeanpetfood.org/about/statistics/>),
- year 2023: cat population is supposed to be the same as in 2022.

• Dogs

- years 1980-1989: based on the register of Finnish Kennel Club and an estimate that 60% of all dogs were registered in 1980's,
- year 1990: single estimate found from the internet,
- years 1991-2003. linear trend assumed between the years 1990 and 2004,
- year 2004: estimate of the Finnish Kennel Club,
- years 2005-2010: linear trend assumed between the years 2004 and 2011,
- year 2011: estimate of the Finnish Kennel Club,
- years 2012-2015: linear trend assumed between the years 2011 and 2016,
- year 2016: Statistics Finland (https://www.stat.fi/til/ktutk/2016/ktutk_2016_2020-04-20_tie_001_en.html),
- years 2017-2020: linear trend assumed between the years 2016-2021,
- years 2021 and 2022: FEDIAF EuropeanPetFood (<https://europeanpetfood.org/about/statistics/>),
- year 2023: dog population is based on the data of the Finnish Kennel Club (<https://www.kennelliitto.fi/tietoa-meista/uutiset/uusi-koirakanta-arvio-kertoo-suomessa-yli-800-000-koiraa-joista-yli-580-000-suomen-kennelliiton-rekisterissa>).

Table 7.2. Estimate on cat and dog annual average population (AAP; thousands) in Finland in 1980-2023.

Year	AAP, cats	AAP, dogs	Year	AAP, cats	AAP, dogs
1980	600	291	2006	596	567
1981	600	318	2007	595	576
1982	600	333	2008	594	584
1983	600	356	2009	594	593
1984	600	369	2010	593	601
1985	600	377	2011	593	610
1986	600	362	2012	592	628
1987	600	395	2013	592	646
1988	600	418	2014	591	664
1989	600	459	2015	591	682
1990	600	510	2016	590	700
1991	600	513	2017	667	712
1992	600	516	2018	744	724
1993	600	519	2019	821	736
1994	600	521	2020	898	748

Year	AAP, cats	AAP, dogs	Year	AAP, cats	AAP, dogs
1995	600	524	2021	975	760
1996	600	527	2022	982	781
1997	600	530	2023	982*	803
1998	600	533			
1999	599	536			
2000	599	539			
2001	598	541			
2002	598	544			
2003	597	547			
2004	597	550			
2005	596	559			

* No data available for 2023, same as for 2022

The uncertainties regarding the total number of cats throughout the entire time series, as well as for dogs during the earlier years (1980-2000), are substantial due to the absence of cat registries and the incomplete coverage of dog registrations in the Finnish Kennel Club's register. However, for the year 2016, there are some statistical estimates available for pet numbers, which have also facilitated estimations regarding the proportion of dogs registered in the Finnish Kennel Club's register.

In 2023, the Finnish Food Authority established a new dog registry in Finland. It is estimated that by the end of 2023, only approximately one third of the dogs were registered.

It's worth noting that while registration with the Finnish Kennel Club is voluntary, the new registry mandated by the Finnish Food Authority is compulsory.

Uncertainty and time series' consistency

The time series is consistent. The results of the uncertainty analysis are provided in Annex 7 of the IIR.

Source-specific QA/QC and verification

Normal statistical quality checks related to the assessment of magnitude and trends have been carried out. At present, no verification has been carried out for the specific source-sector emissions.

Source-specific recalculations including changes in response to the review

2025

- A temperature factor of 0.8 for dogs was added to ammonia emission calculation (see text).

Source-specific planned improvements

The refinement of activity data is an ongoing process.